

SLOWOOD 2.0

SCHEDA TECNICA PRODOTTO - TECHNICAL DATA SHEET

Gres fine porcellanato colorato in massa- Fully-coloured porcelain tiles

DATI GENERALI - GENERAL DATA

SERIE-SERIES :	SLOWOOD
FORMATI-SIZES :	30X120 - 40X120- 60x60
NOMI-NAMES:	GELSO - NOCCIOLO - MANDORLO
COLORI-COLOURS :	GRIGIO - NOCCIOLA - MARRONE GREY - NUT - BROWN
SUPERFICIE-SURFACE :	MAT
NR. COLORI-NR. COLOURS:	3

ACCESSORI - ACCESSORIES

FONDI-TILES :	X	BATTISCOPIA-BULLNOSE:	
DECORI-DECORS:		GRADINO-STEP:	X









USO PREVALENTE - USAGE: Pav. Interno - Pav. Esterno - Riv. Esterno - Riv. Interno

Indoor Floor Tile - Outdoor Floor Tile - Outdoor Wall Tile - Indoor Wall Tile

CARATTERISTICHE TECNICHE - TECHNICAL DATA

Conforme alla norma EN 14411 (ISO 13006) - Compliant with standards EN 14411 (ISO 13006)

Appendice G - Classe di appartenenza B I a - Annex G - Group B I a

RESISTENZA AL GELO FROST RESISTANCE		SI	EN ISO 10545-12
DUREZZA SUPERFICIE (MOHS) HARDNESS (MOHS)		7	UNI EN 101
RESISTENZA ALL'ABRASIONE RESISTANCE TO DEEP ABRASION		≤ 175 mm³	EN ISO 10545-6
SPESSORE THICKNESS		20 mm	EN ISO 10545-2
SCIVOLOSITA' SLIPPERINESS		R 11	DIN 51130
		C (A+B+C)	DIN 51097
		>μ 0,40 Attrito soddisfacente Acceptable Friction	D.M.236-89 Rif. B.C.R.A.
RESISTENZA ALLE MACCHIE RESISTANCE TO STAINING		5	EN ISO 10545-14
RESISTENZA CHIMICA RESISTANCE TO CHEMICALS		UA-ULA-UHA	EN ISO 10545-13
RESISTENZA ALLA FLESSIONE BENDING STRENGTH		≥ 45 N/mm²	EN ISO 10545-4
ASSORBIMENTO WATER ABSORPTION		≤ 0,2%	EN ISO 10545-3